






**To ensure a safe working environment, care must be taken when selecting a pressure gauge or thermometer. The following information can assist with the selection.**

<b>Casing size</b>	To suit the availability of space or reading from a distance. Choose from 50, 63, 80, 100, 120, 150 & 250 mm dia.
<b>Casing type</b>	Choose from bottom or back entry to suit the application. Case material: Stainless steel 304.
<b>Mounting flange</b>	To suit the case size and type for mounting in a panel or against a surface. Choose from front or rear flange. For panel mounting ( front flange, rear entry ) choose from 3 hole flange or slim line front ring with u- bracket.
<b>Wetted parts</b>	These parts must be compatible with the process media. Choose from Cu-alloy ( brass ) or stainless steel 316. for media that will corrode the wetted parts or obstruct the pressure port, a diaphragm type chemical seal should be selected.
<b>Fitting size and positions</b>	To facilitate correct positioning. Choose from 1/8", 1/4", 3/8", or 1/2" BSP or NPT at the bottom or rear of the case.
<b>Working pressure</b>	Although pressure gauges will tolerate full scale pressure for short periods, in general the working pressure should not exceed 70% of the full scale value of the pressure gauge. For thermometers, media pressure should not exceed 2500 kPa without the use of a suitable thermowell.
<b>Media temperatures</b>	For pressure gauges, media temperature should not exceed 70°C. If so, choose from a syphon tube, cooling element, capillary assembly or diaphragm seal to isolate the gauge from media. For thermometers, select the temperature range double that of the media operating temperature.
<b>Working conditions</b>	Adverse working conditions such as vibration, pulsation and shock loads, require the use of a dampening device. Choose from glycerine/ silicone filling, a snubbing device or capillary assembly to remove the instrument from the cause.
<b>Fitting types</b>	<ol style="list-style-type: none"> <li>1) BSP ( parallel ) thread seals by means of the seat at the end of the thread. It is advisable to use copper or another suitable sealing washer to ensure a good seal. ( see diagram 1 )</li> <li>2) BSPT / NPT ( taper ) thread seals by means of the mating of the thread. PTFE ( teflon ) tape or any other suitable jointing material will ensure a good seal. ( see diagram 2 )</li> </ol>
<b>Installation</b>	<p>Always secure the instrument by means of a suitable wrench on the hexagon/square of the threaded connection. <b>Twisting the instrument by hand on the case can cause damage to the internals of the instrument.</b> ( see diagram 3 )</p> <p>For gauges with flanges to facilitate panel or surface mounting, please support gauge fitting with a suitable size wrench to counter the force of tightening the process fitting, this will prevent damaging the gauge internals.</p>



## INDEX

Page 1 - Pressure - Industrial Use - General Purpose	Page 20 - Thermometer - Bimetal - Airconditioning / Heating Series
Page 2 - Pressure - Process Industry Use	Page 21 - Thermometer - Machine - V Line
Page 3 - Pressure - Capsule Gauge - Low Pressure	Page 22 - Diaphragm Seals - General Industrial Use - CS70
Page 4 - Pressure - Refrigeration Gauge	Page 23 - Diaphragm Seals - Food / Hygiene Series
Page 5 - Pressure - Diaphragm Operated Gauge	Page 24 - Flanged Diaphragm Seals
Page 6 - Pressure - Test Gauge - Mirror Dial	Page 25 - Pressure Accessories - Gauge Cocks, Adaptors, Syphon Tubes, Capillary Assemblies, Cooling Towers & Rubber Covers
Page 7 - Pressure - Tyre Gauge	Page 26 - Dimensions - Pressure Gauge - Rolled Ring Case - General Industrial Use
Page 8 - Pressure - Electrical Contact - Magnetic Type	Page 27 - Dimensions - Pressure Gauge - Bayonet Twist Case - Process Series
Page 9 - Pressure - Electrical Contact - Micro Switch	Page 28 - Dimensions - Pressure Gauge - Diaphragm Operated
Page 10 - Pressure - Locomotive Gauge RW4	Page 29 - Dimensions - Thermometer - Bimetal Process Series
Page 11 - Pressure - Locomotive Gauge RW6	Page 30 - Dimensions - Thermometer - Gas Actuated Series
Page 12 - Pressure - Mining Gauge - Staple Lock	Page 31 - Dimensions - Thermometer - Vapour Expansion Series
Page 13 - Pressure - Safety Gauge - Solid Front	Page 32 - Dimensions - Diaphragm Seals - CS70
Page 14 - Pressure - Duplex Gauge	Page 33 - Dimensions - Diaphragm Seals - Food / Hygiene Series
Page 15 - Pressure - Transmitter	Page 34 - Standard Gauge Scale Ranges
Page 16 - Pressure - Testing Kits	Page 35 - Test Gauge Scale Ranges
Page 17 - Thermometer - Bimetal - Process Industry Series	
Page 18 - Thermometer - Gas Actuated Series	
Page 19 - Thermometer - Vapour Expansion Series	